

DE 45 BLACK (STE)

INSTANTANEOUS WATER HEATER FOR SHOWERS

PRODUCT-NO.: 205606

Supreme matte black to complete your bathroom

A compact instantaneous water heater supplies domestic hot water on demand, with pure elegance in 100% matte black, compact design for space-saving and complimenting or contrasting your bathroom interior. Fully functional at an affordable price.

Suitable to your style



The main features

LED light on the appliance cover shows when Power “ON”

Stepless temperature adjustment

Non-slip power selector

Highly efficient composite polymer tank for reduced heat loss and electricity consumption

5-in-1 shower head with slide bar for convenient height adjustment

Compact design for space saving installation

Automatic on/off control with flow switch

Flame-retardant electronic circuit board for extra safety

Suitable for operation with low water pressure

Protection from electric shock with Earth Leakage Sensing Device (ELSD)

Protection class IP25 (splash-proof)

Quick and easy installation

LED light on the appliance cover shows when Power “ON”



DE 35 BLACK (STE)

Product-No.: 205605

Step-less temperature adjustment

Non-slip power selector

Highly efficient composite polymer tank for reduced heat loss and electricity consumption

5-in-1 shower head with slide bar for convenient height adjustment

Compact design for space saving installation

Automatic on/off control with flow switch

Flame-retardant electronic circuit board for extra safety

Suitable for operation with low water pressure

Quick and easy installation

Protection from electric shock with Earth Leakage Sensing Device (ELSD)

Protection class IP25 (splash-proof)



Type	DE 35 BLACK (STE)	DE 45 BLACK (STE)
Part no.	205605	205606

Technical data

Cold water connection	1/2 inch	1/2 inch
Electrical fuse protection	ELSD	ELSD
Rated output	3,500 W	4,500 W
Electrical connection	1/N/PE~220-240 V	
Rated voltage	220-2240 V	
Rated current	15.9 A	20.4 A
Display	without	without
Heating element	Copper tubular	Copper tubular
Type	Open outlet	Open outlet
Automatic flow switch	true	true
Heating material	Plastic	Plastic
Temperature setting	Step-less	Step-less
Temperature control	Power control	Power control
Anti-scalding protection	Double acting thermostat	Double acting thermostat
Shower accessories	5-in-1 shower head with wall mounting bracket	5-in-1 shower head with wall mounting bracket

Colour	black	white
IP rating	IP25	IP25
Shutdown value	0.8 l/min	0.8 l/min
Starting flow rate	1.3 l/min	1.3 l/min
Depth	78 mm	78 mm
Height	308 mm	308 mm
Width	184 mm	184 mm
Weight	1 kg	1 kg

Contact information

You have questions? We appreciate to help you:

Call 02-021-9300

Write an email to th-info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.