

WS 35 E-2 (STE)

INSTANTANEOUS WATER HEATER FOR SHOWERS

PRODUCT-NO.: 203185

The main features

Temperature adjustment via stepless power control

Complete set optimised for a single shower

Corrosion-free copper heating element for longer service life

5-in-1 shower head with slide bar for convenient height adjustment

Anti-scalding and overheating protection with double action thermostat

Protection from electric shock with Earth Leakage Sensing Device (ELSD)

Protection class IP25 (splash-proof)



WS 45 E-2 (STE)

Product-No.: 203186



WS 55 E-2 (STE)

Product-No.: 203187



| | | | |
|----------|-----------------|-----------------|-----------------|
| Type | WS 35 E-2 (STE) | WS 45 E-2 (STE) | WS 55 E-2 (STE) |
| Part no. | 203185 | 203186 | 203187 |

Technical data

| | | | |
|----------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| Cold water connection | 1/2 inch | 1/2 inch | 1/2 inch |
| Electrical fuse protection | ELSD | ELSD | ELSD |
| Rated output | 3,500 W | 4,500 W | 5,500 W |
| Electrical connection | 1/N/PE~220-240 V | 1/N/PE~220-240 V | 1/N/PE~220-240 V |
| Rated current | 15.9 A | 20.5 A | 25 A |
| Display | Standard | Standard | Standard |
| Heating element | Copper tubular | Copper tubular | Copper tubular |
| Type | Open outlet | Open outlet | Open outlet |
| Automatic flow switch | true | true | true |
| Heating material | Copper | Copper | Copper |
| Temperature setting | Variable | Variable | Variable |
| Temperature control | Output control | Output control | Output control |
| Anti-scalding protection | Double acting thermostat | Double acting thermostat | Double acting thermostat |
| Shower accessories | 5-in-1 head shower with slide bar | 5-in-1 head shower with slide bar | 5-in-1 head shower with slide bar |
| Colour | white | white | white |
| IP rating | IP25 | IP25 | IP25 |

| | | | |
|---------------------------|------------------|------------------|------------------|
| Shutdown value | 0.8 l/min | 0.8 l/min | 1.3 l/min |
| Starting flow rate | 1.3 l/min | 1.3 l/min | 2.2 l/min |
| Depth | 79 mm | 79 mm | 79 mm |
| Height | 326 mm | 326 mm | 326 mm |
| Width | 200 mm | 200 mm | 200 mm |
| Weight | 1.4 kg | 1.4 kg | 1.5 kg |

Contact information

You have questions? We appreciate to help you:

Call 02-021-9300

Write an email to th-info@stiebel-eltron.com

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.